



Reef Scuba Accessories

905 Shillelagh Road, Chesapeake, VA 23323 USA



Made in USA
Our Service Policy

Privacy Statement

To Bookmark this Site, Press Cltr + D

In US: Call 1-800-633-4837

International: Call +011-757-436-7664

Fax: 1-757-547-2100

The Pony Tamer®
►Tamer Parts/Upgrades
The X-Bracket®
Dive Reels
►Dive Reels
Modules/Parts
►Rope Specifications
Rope and Webbing
Solid Brass Hardware
Stainless Steel Hardware
Technical Hardware
Tank Accessories
Neoprene Products
Surgical Tubing
►Tubing Specifications
Bungee Elastic Cord
►Bungee Accessories
►Bungee Load Specs
O-Rings
Plastic & Rubber Products



Additional Accessories
New Products
Specials
Feedback
Links
Internet Tips
For Your Information
A Little Humor/Wisdom
Sudden Facts

Safe, Easy & Satisfying
Online Sales
Your Security Statement



Click Here to Check Out "The Survivor Reel"

- Secure, easy online sales, cash saving--New products constantly being added.
- Save your money with easy-to-use, field tested "patented" products.
- Everything in life is--or can be a learning experience.



You will always receive fast and dependable customer service from experts who genuinely want to help at Reef Scuba Accessories. We have qualified and experienced individual consulting available for you on any of our products.

Please give us a call at 1-800-633-4837 in the U.S. or call 1-757-436-7664 for international calls.

Universal Currency
Converter™

Office Hours:
Monday through Friday
8:30 a.m.- 5:00 p.m. EST

There is an incredible amount of knowledge here from which to learn. "An educated person is our best customer." Please browse through our website and visit our extensive "Links" area.

Reef Scuba Accessories, Inc., Chesapeake, VA 23323 USA
Copyright ©1990-2003 All rights reserved worldwide.
Revised: April 21, 2003



Surgical Tubing Specifications



In USA: 800-633-4837

International: +011-757-436-7664

Fax: 757-547-2100

[Back to Surgical Tubing Page](#)
[Reef Scuba Accessories, Inc.](#)
[Home Page](#)
[r Bottom of Page \(Menu\)](#)

Quality Assurance: All latex surgical tubing is produced in accordance with the FDA's Quality System Regulation (QSR).

Physical Properties:

- **Standard Colors:** Black or Amber
- **Tensile Strength:** 3,500 PSI Minimum
- **Elongation at Break:** 750% Minimum
- **Modulus at 300%:** 190 PSI Maximum
- **Shore A Durometer Hardness:** 35±5
- **Specific Gravity:** 0.95

Temperature/Chemical Resistance

- **Minimum recommended operating temperature:** -65°F (-53°C)
- **Maximum recommended operating temperature:** 180° F (82°C)
- **Chemical resistance to:**
 - Acid (dilute): Fair to Good
 - Acid (concentrate): Fair
 - Alkali: Good
 - Petroleum Products Not recommended
- **Heat-aging resistance:** Good

The physical properties of our natural latex rubber tubing meet or exceed all Federal regulations for performance, including Federal Specifications ZZZ-T-831D, Amendment Four, Types I, III, IV and V, Class 1, 2, and 3 translucent and black, and Military Specification MIL-T-36966. In addition, tubing undergoes biocompatibility testing on a regular basis.

[Back to Surgical Tubing Page](#)
[▲ Top of Page](#)
[Home Page](#)
[The Pony Tamer® & The X-Bracket®](#)
[Dive Reels](#)
[Bunge Elastic Shock Cord](#)